

10/593,113

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/IL2006/000678

International filing date: 11 June 2006 (11.06.2006)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/689,147
Filing date: 10 June 2005 (10.06.2005)

Date of receipt at the International Bureau: 02 August 2006 (02.08.2006)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

PCT/IL2006/000678
20 JUL 2006

PA 1486225

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

July 05, 2006


THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/689,147

FILING DATE: June 10, 2005

THE COUNTRY CODE AND NUMBER OF YOUR PRIORITY APPLICATION, TO BE USED FOR FILING ABROAD UNDER THE PARIS CONVENTION, IS US60/689,147

By Authority of the
Under Secretary of Commerce for Intellectual Property
and Director of the United States Patent and Trademark Office



A handwritten signature in dark ink, appearing to read "P. Swain", is written over the printed name.

P. SWAIN
Certifying Officer

061005

21661 U.S. PTO

PTO/SB/16 (04-05)

Approved for use through 07/31/2006. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. _____

INVENTOR(S)		
Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)
GIL	NAOR	Ramat Hasharon, ISRAEL
Additional inventors are being named on the _____ separately numbered sheets attached hereto		
TITLE OF THE INVENTION (500 characters max):		
Permanent Cerebral Embolic Protection Device		
Direct all correspondence to: CORRESPONDENCE ADDRESS		
<input type="checkbox"/> The address corresponding to Customer Number: _____ OR <input checked="" type="checkbox"/> Firm or Individual Name <u>SagaX Inc.</u> Address <u>20 Galgaley Haplada st. P.O. Box 12240</u> City <u>Herzlia Pitvach</u> State _____ Zip <u>46722</u> Country <u>ISRAEL</u> Telephone <u>972-9-9508089</u> Email <u>gi@sagaxmed.com</u>		
ENCLOSED APPLICATION PARTS (check all that apply)		
<input checked="" type="checkbox"/> Application Data Sheet. See 37 CFR 1.76 <input checked="" type="checkbox"/> Specification Number of Pages <u>6</u> <input checked="" type="checkbox"/> Drawing(s) Number of Sheets <u>2</u> <input type="checkbox"/> CD(s), Number of CDs _____ <input type="checkbox"/> Other (specify) _____		
Application Size Fee: If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$250 (\$125 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).		
METHOD OF PAYMENT OF FILING FEES AND APPLICATION SIZE FEE FOR THIS PROVISIONAL APPLICATION FOR PATENT		
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. <input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fee and application size fee (if applicable). <input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached. <input type="checkbox"/> The Director is hereby authorized to charge the filing fee and application size fee (if applicable) or credit any overpayment to Deposit Account Number: _____. A duplicative copy of this form is enclosed for fee processing.		
TOTAL FEE AMOUNT (\$) <u>\$ 100</u>		
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.		
<input type="checkbox"/> No. <input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____		

SIGNATURE _____

Date May 22, 2005TYPED or PRINTED NAME Gil Naor

REGISTRATION NO. _____

TELEPHONE 972-54-5705061(if appropriate)
Docket Number: _____**USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT**

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PROVISIONAL APPLICATION COVER SHEET
Additional Page

PTO/SB/16 (04-05)

Approved for use through 07/31/2006. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

First Named Inventor	GIL NAOR	Docket Number	
INVENTOR(S)/APPLICANT(S)			
Given Name (first and middle [if any])	Family or Surname	Residence (City and either State or Foreign Country)	
GIL	NAOR	4 Haziporen st. Ramat-Hasharon, 47284 ISRAEL	
Dov	Shimon	57 Hapoel st. Herzlia Pitvach 46600 ISRAEL	
Michael	Ortenberg	60/2 Negav st. P.O. Box 2090 Kfar-Iona 40300 ISRAEL	

Number 2 of 2

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Provisional Application

Inventors:

Gil Naor, Ramat Hasharon, Israel

Dov Shimon, MD Nof Yam, Israel

Michael Ortenberg, Kfar Yona, Israel

PERMANENT CEREBRAL EMBOLIC PROTECTION

FIELD AND BACKGROUND OF THE INVENTION

The present invention relates to permanent cerebral embolic protection by a way of diverting the particulate originating in the heart and traveling in the blood flow to the Aorta, to the lower extremities.

Described are devices and methods for diverting emboli away from the carotid arteries in the aorta. The devices are aortic diverters that generally comprise a hollow tube with a substantially cylindrical, spherical or conical wall, which is impermeable to emboli and which has open ends that allow blood to enter one end, flow through the tube and exit the other end. Additionally, aortic diverters, which are planar rather than cylindrical are also shown. The methods of the invention generally include the steps of providing an aortic diverter carried by an intravascular catheter, introducing the intravascular catheter into the vascular system, advancing the intravascular catheter into the aortic arch and into the carotid arteries, and deploying the aortic diverter.

WHAT IS CLAIMED IS:

1. A method for protecting a patient against cerebral embolization wherein the diverter is secured to the lumen of one of the cerebral arteries branching from the aorta and is protruding to the aorta lumen:

(a) a first substantially tubular embodiment that is curved downstream of the aorta

(b) a second substantially spherical and which has an opening directed at the downstream of the aorta.

(c) a third substantially planner and which is secured in both the cerebral branch and in the descending aorta

2. The protection device of claim 1, wherein the whole embodiment is temporarily deformable to assume a delivery state in a reduced diameter size to allow delivery through a minimally invasive delivery system.

SUMMARY OF THE INVENTION

The present invention provides different embodiments for cerebral protection of emboli by diverting them from entering the cerebral branches to the lower extremities. The devices are anchored in the cerebral branches and have the effective filtering part protruding into the aorta lumen.

As the device is deployed within the cerebral branch vessel from the end of the catheter, it is designed to expand radially against the vessel's inner walls, and exert a certain amount of pressure in order to retain its positioning, even as the vessel may be prone to dilate elastically.

The amount of acceptable vessel dilation that may be accommodated is determined by the relative dimensions of the structure and vessel, the structure used and properties of the materials from which the structure is constructed.

As the device is further deployed, the filtering section unfolds into the aorta lumen in such a way as to divert any particles above a given size from entering the carotid branches. The device has an open end to allow for future interventions to take place and to not create a "jailed artery".

The structure may be fabricated in linear form from a single piece of material, by way of laser cutting or etching, avoiding joining mechanisms that may compromise the material properties. The structure may also be constructed from individual pieces (wires), and may or may not be accommodated by an additional filtering netlike mesh.

The structure is constructed from a material with (but not limited to) appropriate shape memory and/or superelastic properties.

Prior to deployment, the catheter end is positioned inside the vessel at a desired point for deployment. The structure is then deployed from the end of the catheter by suitable means, such that the portion which emerges unfolds gradually as it is no longer restrained by the catheter's walls. The folded

configuration of the structure within the catheter is configured such that, as the structure is deployed, it expands to press against the vessel's inner walls in the anchoring part, and regain its predetermined shape in the aorta lumen.

The folded structure is designed to fit a catheter of reasonable size to the application, and to be smooth sided in order to slide freely within the catheter through potentially tortuous paths and overcome the inevitable resistance caused by its affinity to expand.

Various forms of configurations may be used to allow the device to be collapsed inside a catheter. Three preferred configurations described herein below with reference to Figures 1-6.

The first substantially preferred embodiment (figure 1A-1B and 2A-2B) is a simple tube either straight or bended and which is open on both ends.

The second substantially preferred embodiment (figure 3A-3B) has a spherical shape in the aorta lumen and has an opening directed at the downstream of the aorta flow.

The third substantially preferred embodiment (figure 4A-4B) has an anchor in the carotid artery and an anchor in the descending aorta distal to the left carotid, and a linear section in between that acts as the filtering part.

Those skilled in the art will appreciate that the curvature of the device and the design of each section may be varied widely to serve the purposes of a given application. Thus, according to the teachings of the present invention there is provided, a cerebral embolic protection device, the device comprising:

(a) a first substantially closed tubular section configured to assume a shape lying substantially on a virtual cylinder of given diameter which acts as the anchoring part; and (b) a second substantially tubular or spherical or linear section which acts as the filtering part.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is herein described, by way of example only, with reference to the accompanying drawings, wherein:

has a tubular shape (either straight or curved) anchored in the carotid and protruding into the aorta lumen, the anchoring section has a design which virtually applied enough radial pressure on the vessel wall as to avoid migration or tilting of the device, and the section which protrude into the aorta lumen is designed as a filter with a predetermined porosity. The tubes can be cut by laser from a tube of a specific dimensions

FIG. 1A is a schematic side view of a first preferred configuration of the Protective device, in which the filtering section is a partial cylindrical shape that is opened on one end to allow for blood to enter the carotid artery.

FIGS. 1B is a schematic side view of the embodiment of figure 1A implanted in the Innominate artery (by way of an example), protruding into the aorta.

FIG. 2A is a schematic side view of the first preferred configuration of the Protective device, in which the filtering section is curved towards the aorta downstream.

FIGS. 2B is a schematic side view of the embodiment of figure 2A implanted in the Innominate artery (by way of an example), protruding into the aorta.

FIG. 3A is a schematic side view of a yet another preferred configuration of the Protective device, in which the filtering section is spherical or "mushroom" shaped and has an open section on one end to allow for blood to enter the carotid artery.

FIGS. 3B is a schematic side view of the embodiment of figure 3A implanted in the Innominate artery (by way of an example), protruding into the aorta.

FIG. 4A is a schematic side view of a yet another preferred configuration of the Protective device, in which the filtering section is a planner in shape and is anchored at both ends by stent like sections at the carotid artery and the ascending aorta.

FIGS. 4B is a schematic side view of the embodiment of figure 4A implanted in the Innominate artery (by way of an example) and ascending aorta.

FIG. 5 is a schematic side view of yet another preferred configuration of the Protective device, in which the filtering section is a fully cylindrical in shape that is opened on one end to allow for blood to enter the carotid artery and is made of braided wires of differing diameters.

FIG. 6 is a schematic side view of the preferred configuration of figure 5 of the Protective device, in which the device is made of a platform of netlike structure and an additional net of a predetermine mesh.

Even within the individual implementations described herein, the devices of the present invention are believed to include numerous different aspects each of which is believed to be susceptible to patent protection individually. Thus, it should be appreciated that features of the invention indicated herein to be of particular importance should not necessarily be interpreted as necessary to all aspects of the invention, but rather according to the specific combinations of features as defined by the appended claims.

Drawings




Figure 1A




Figure 1B




Figure 2A




Figure 2B




Figure 3A




Figure 3B




Figure 4A




Figure 4B




Figure 4A




Figure 5B




Figure 6A